



Official Website

NOBLELIFT
AUSTRALIA

Add: 116 Forrester Rd, St Marys, NSW
2760, Australia
Tel: 1300 123 999
Email: sales@noblelift.com.au
Web: noblelift.com.au

NOBLELIFT
Material Handling

ISO9001 / ISO14001
// 2020.01

FE4P16/20Q



-wheel Electric forklift



NEW Noblelift Products
ARRIVAL

noblelift.com.au

AC MAINTENANCE-FREE DRIVE MOTOR

Adopt maintenance-free and powerful AC drive motor. Compared with traditional DC motors, Noblift's AC motors do not need to replace Carbon brushes. Equipped With speed sensor and temperature sensor, greatly improving the AC motor's reliability.

SIDE- EXTRACTION BATTERY

Battery can be replaced easily by using another forklift, meeting continuous application if necessary.

LOW CENTER OF GRAVITY

Transmission system uses a horizontal fan-shaped drive Axle arranged in parallel and has a large transmission ratio. The battery is installed at the bottom of the frame, vehicle height is 2080mm with easy entrance to limited doors and high stability.

LOW NOICE, LOW VIBRATION DESIGN


The hydraulic system uses a low-noise gear pump and full hydraulic power steering. Low noise and comfortable operation.
Steering axle vibration absorb design: adopt flexible connection to protect the vehicle system and prolong the service life of the forklift

SAFER AND EASIER ELECTROMAGENTIC BRAK

Adopt car control mode and electromagnetic braking to make the driver's operation more comfortable.



The design of the Q series is based on the original Noblift E series and N series with combination of the advantages to meet the light and medium applications with great comfortness and efficiency. The truck is optional to have either Lead-acid battery or Li-ion battery. With lowered center of gravity and overhead guard, the truck is ideal to be used in limited spaces such as entering elevator.



Transmission system uses a horizontal fan-shaped drive axle arranged in parallel with a large transmission ratio. The battery is installed at the bottom of the frame. Traveling motor adopts AC maintenance-free motor.

Front multi-way valve operating device makes operation more comfortable.



Steering axle vibration absorb design: adopt flexible connection to protect the vehicle system and prolong the service life of the forklift.



Adopt car control mode: Suspended driving brake system, stepless speed change. Finding driving pleasure at work.



Multi-function display screen with fault alarm, low battery reminder. High, medium and low speed modes.

Electromagnetic brake button cut off power at one time, making brake safer and easier.



A The vehicle hood and the left and right small side-panels are formed by steel plates at one time, which is simple and decent and more convenient to operate.

B Wide-view mast, intelligent buffering when descending to the ground, effectively protecting the ground and cargo from damage.

C The forklift is equipped with standard LED lamps: headlamps, front turn lamps, rear combination lamps, warning lamps. Bright light with low power consumption allows you to operate freely at night.

D Compared with other N series 4-wheel Electric counter balance forklift, this model is smaller in size and more flexible, which is more suitable for working in narrow places

Mast Table FE4P16-20Q							
Designation	Lift height	Free Lift	Closed mast height	Extended mast height	Tilt forward/ backward $\alpha/\beta(^{\circ})$	Capacity table(kg) C=500mm without sideshift, single solid tyres	
	h3 (mm)	h2 (mm)	h1 (mm)	h4 (mm)		FE4P16Q	FE4P20Q
Two-stage ZT	2500	110	1803	3482	6/10	1600	2000
	2700	110	1903	3682	6/10	1600	2000
	3000	110	2053	3982	6/10	1600	2000
	3300	110	2203	4282	6/10	1600	2000
	3500	110	2303	4482	6/10	1600	2000
	3700	110	2403	4682	6/10	1600	1900
	4000	110	2603	4982	6/6	1500	1800
	4300	110	2753	5282	6/6	1400	1600
	4500	110	2853	5482	6/6	1350	1500
	5000	110	3128	5982	6/6	900	1100
Two-stage ZZ	2500	853	1803	3482	6/10	1600	2000
	2700	953	1903	3682	6/10	1600	2000
	3000	1103	2053	3982	6/10	1600	2000
	3300	1253	2203	4282	6/10	1600	2000
	3500	1353	2303	4482	6/10	1600	2000
	3700	1453	2403	4682	6/10	1600	1900
	4000	1653	2603	4982	6/6	1500	1800
Three-stage DZ	4000	1029	1978	4981	6/6	1500	1800
	4300	1153	2103	5330	6/6	1400	1600
	4500	1203	2153	5480	6/6	1300	1500
	4800	1303	2253	5780	6/6	1000	1200
	5000	1403	2353	5980	6/6	900	1100



Fast replacement of the battery can meet continuous operation. The fully open hood design makes daily maintenance very convenient.

Lead-acid and lithium batteries are perfectly interchangeable. Don't worry about which battery to choose now.



FE4P16-20Q Battery Balance Weight Type Forklift

Identification				
1.1	Manufacture(abbreviation)		Noblelift	
1.2	Manufacturer's type designation		FE4P16Q	FE4P20Q
1.3	Drive:electric(battery or mains),diesel,petrol gas,manual)		electric	
1.4	Type of operation(hand,pedestrian,standing,seated,order-picker)		seated	
1.5	Load capacity/rated load	Q(kg)	1600	2000
1.6	Load centre distance	C(mm)	500	
1.8	Load distance,centre of drive axle to fork	x(mm)	381	386
Weights				
2.1	Service weight incl. battery	kg	2940	3180
Wheels, Chassis				
3.1	Type:solid rubber,superelastic,pneumatic,polyurethane		solid rubber/pneumatic	
3.2	Tyres size,front		18X7-8	
3.3	Tyres size,rear		5.00-8-10PR	
3.5	Wheels,number front/rear(\times =driven wheels)		2 \times 2	
3.6	Track width,front	b10(mm)	980	
3.7	Track width,rear	b11(mm)	920	
Basic Dimensions				
4.1	Mast/fork carriage tilt forward/backward	$\alpha/\beta(^{\circ})$	6/10	
4.2	lowered mast height	h1(mm)	1985	
4.3	Free lift	h2(mm)	130	
4.4	Lift height	h3(mm)	3000	
4.5	Extended mast height	h4(mm)	3990	
4.7	Overhead load guardheight	h6(mm)	2075	
4.8	Seat height/standing height	h7(mm)	1065	
4.12	Coupling height	h10(mm)	530	
4.19	Overall length	l1(mm)	3050	3200
4.20	Length to face of forks	l2(mm)	2130	
4.21	Overall width	b1(mm)	1150	
4.22	Fork dimensions	s/e/l(mm)	35/100/920	40/120/1070
4.24	Fork carriage width	b3(mm)	1040	
4.31	Ground clearance ,laden,under mast	m1(mm)	98	
4.32	Ground clearance,centre of wheelbase	m2(mm)	100	
4.33	Aisle width for pallets 1000 \times 1200 crossways	As(mm)	3571	3576
4.34	Aisle width for pallets 800 \times 1200 lengthways	As(mm)	3771	3776
4.35	Turning radius	Wa(mm)	1990	
Performance Data				
5.1	Travel speed,laden/unladen	km/h	12/13	11/13
5.2	Lift speed,laden/unladen	m/s	0.27/0.35	0.25/0.35
5.3	lowering speed,laden/unladen	m/s	0.52/0.42	
5.7	Max.Gradient performance,laden/unladen S2.5 min	%	12/15	
5.10	Service brake		electromagnetic brake	
E-Motor				
6.1	Drive motor rating S2 60 min	kW	7	
6.2	Lift motor rating at S3 15%	kW	8.6	
6.3	Battery standard		DIN	
6.4	Battery voltage,nominal capacity K5	V/Ah	Pb-acid:48/360(48/400,48/460) Li:48/200(48/300,48/400)	Pb-acid:48/400(48/460) Li:48/200(48/300,48/400)
Other Details				
8.1	Type of drive control		AC	
8.2	Operating pressure for attachments	Mpa	14.5	
8.3	Oil volume for attachments	l/min	30	
8.4	Sound level at driver's ear according to EN 12 053	dB(A)	72	